

REFERENCE STANDARD CASSETTE MECHANISM

The construction of the Reference Cassette mechanism is a singular achievement in cassette technology. The main frame is a one piece, die cast alloy mounted between transparent, hard plastic plates. The entire assembly is locked together with six computer torqued, double threaded screws. Clear liner sheets aid in viewing tape travel. All of the features of the Super Precision Cassette Mechanism are included.

Tape
Selector

Metal
(TYPE IV)

Bias: Metal
EQ: 70 μ s

This cassette tape should only be used on a cassette recorder which has a metal bias position.


TDK MA-R90 (135m) 90min. @ 1-7/8ips (2 X 45min.)

**MA-R METAL ALLOY
CASSETTE**

90

TDK METAL TAPE fully realizes the dramatic advantages of metal alloy over conventional tape. Its far superior MOL and freedom from high frequency saturation deliver more vibrant recordings of wider dynamic range than were previously possible on cassettes. The long term stability of TDK FINAVINX metal particles is assured

through a unique polymer coating which permanently seals each one.



UK. PAT. 989987 F.R. GERMANY PAT.MR 15634
FRANCE PAT 77598 TAIWAN PAT 3728

TDK Cassettes are manufactured and shipped under the strictest quality control standards. If this product proves to be defective in materials or workmanship, it will be replaced. This warranty does not affect the statutory rights of the consumer. (Effected only in U.K.)

Note: TDK will not be liable for any injury, loss or damage, direct or consequential, arising out of the use of, or the inability to use, this product.

TDK CORPORATION
13-1, Nihonbashi 1-chome, Chuo-ku, Tokyo 103, Japan
TDK TAPE DISTRIBUTOR (U.K.) Limited
Pembroke House, 44 Wellesley Road, Croydon, Surrey, CRO 9XW, U.K.
TDK (AUSTRALIA) PTY. LTD.
Unit 2, Level A South, 100 Harris Street, Pyrmont, N.S.W. 2009, Australia

©1982 TDK CORPORATION

**Compact
Cassette**

MADE IN JAPAN
700254

Tips on Handling and Storage

- 1 Avoid touching the tape with your fingers: you may cause drop-outs or scratches.
- 2 Protect your cassette from dust and damage when not in use by keeping it in its protective plastic box.
- 3 The tape should be wound snugly on the cassette reels, if the tape is loose, carefully wind it on to one of the reels by gently turning one of the hubs.

4 Keep the recorder head and pinch roller clean by regular use of a good cassette head cleaner (like TDK's HC-1, head cleaner cassette).

5 Avoid prolonged exposure of cassettes to excessive heat (should be kept below 110°F/45°C), humidity, direct sunlight and strong magnetic fields. Do not store near hearing appliances, TV sets or similar equipment.

After completing the information on this card, tear it off and file it for an instant record of your cassette library's contents.



MONO/STEREO | BIAS/EQ | Noise Reduction IN OUT

DATE | TIME

NO. | TITLE

RECORDING MEMORANDUM

A Noise Reduction
EQ Metal : 70 μ s

B Noise Reduction
EQ Metal : 70 μ s



NO.